

FOOT PEDAL

**ACCESSORIES
MANUAL PNEUMATIC DISTRIBUTOR**



The foot pedal valve with guard is available with bistable or monostable version, 3 or 5 ways and 1/4" connection. The valve has zamak body, the guard is made of nylon. The mounting is possible by holes in valve body.

TECHNICAL DATA

FLOW RATES

Flow rate NI/min.	490	580	700	800	920
Pressure bar	3	4	5	6	7

CONSTRUCTIVE FEATURES

Ports	1/4"
Ways	3/2 - 5/2
Functions	Foot valve
Body	Zamak
Seals	Nitrilic rubber NBR
Protection	Nylon
Mounting	Holes on valve body



TECHNICAL DATA



Fluid	Filtered air
Lubrication	With or without lubrication
Lubricant	Compatible with NBR (3°÷10° E) class H

TECHNICAL FEATURES

Operating pressure	1 ÷ 10 bar
Temperature range	-10°C +50°C

RANGE

	Symbol	Port	Model
3/2 WAYS SPRING PILOT		1/4"	36357
3/2 WAYS DOUBLE PILOT		1/4"	36367

5/2 WAYS SPRING PILOT		1/4"	36359
5/2 WAYS DOUBLE PILOT		1/4"	36369

DIMENSIONS

